

BLMA

1 ... 4 GHz

Solid State

Standard Models

Model	Frequency Range	Output Power P_N min W	Gain min / typ dB	Harmonics 2nd / 3rd dBc	Line Power W	Dimensions (H, D) 19"-System	Weight kg
BLMA 1040-30/20D	1 ... 4 GHz	30/20			200	3 HU, 550 mm	20
	1 ... 2 GHz	30	44.8 / 47 $\pm$ 2	20 / 20			
	2 ... 4 GHz	20	43 / 45 $\pm$ 2	20 / 20			
BLMA 1040-30D	1 ... 4 GHz	30/30			350	3 HU, 630 mm	23
	1 ... 2 GHz	30	44.8 / 47 $\pm$ 2	20 / 20			
	2 ... 4 GHz	30	44.8 / 47 $\pm$ 2	20 / 20			
BLMA 1040-60/35D	1 ... 4 GHz	60/35			500	3 HU, 630 mm	23
	1 ... 2 GHz	60	47.8 / 50 $\pm$ 2	20 / 20			
	2 ... 4 GHz	35	45.4 / 48 $\pm$ 2	20 / 20			
BLMA 1040-60D	1 ... 4 GHz	60/60			600	3 HU, 630 mm	26
	1 ... 2 GHz	60	47.8 / 50 $\pm$ 2	20 / 20			
	2 ... 4 GHz	60	47.8 / 50 $\pm$ 2	20 / 20			
BLMA 1040-100/60D	1 ... 4 GHz	100/60			750	3 HU, 630 mm	28
	1 ... 2 GHz	100	50 / 52 $\pm$ 2	20 / 20			
	2 ... 4 GHz	60	47.8 / 49 $\pm$ 2	20 / 20			
BLMA 1040-100D	1 ... 4 GHz	100/100			1300	6 HU, 630 mm	45
	1 ... 2 GHz	100	50 / 52 $\pm$ 2	20 / 20			
	2 ... 4 GHz	100	50 / 52 $\pm$ 2	20 / 20			
BLMA 1040-200/100D	1 ... 4 GHz	200/100			1300	6 HU, 630 mm	45
	1 ... 2 GHz	200	53 / 55 $\pm$ 2	20 / 20			
	2 ... 4 GHz	100	50 / 52 $\pm$ 2	20 / 20			
BLMA 1040-200D	1 ... 4 GHz	200			3200	10 HU, 630 mm	85
	1 ... 2 GHz	200	53 / 55 $\pm$ 2	20 / 20			

BONN Elektronik GmbH – BLMA 1 ... 4 GHz

	2 ... 4 GHz	200	53 / 55 ±2	20 / 20			
BLMA 1040–240/200D	1 ... 4 GHz	240/200			2700	10 HU, 630 mm	75
	1 ... 2 GHz	240	53.8 / 56 ±2	20 / 20			
	2 ... 4 GHz	200	53 / 55 ±2	20 / 20			
BLMA 1040–400/200D	1 ... 4 GHz	400/200			2700	13 HU, 630 mm	105
	1 ... 2 GHz	400	56 / 58 ±2	20 / 20			
	2 ... 4 GHz	200	53 / 55 ±2	20 / 20			
BLMA 1040–400D	1 ... 4 GHz	400/400			6500	20 HU, 630 mm	180
	1 ... 2 GHz	400	56 / 58 ±2	20 / 20			
	2 ... 4 GHz	400	56 / 58 ±2	20 / 20			
BLMA 1040–750/400D	1 ... 4 GHz	750/400			9000	30 HU, 630 mm	230
	1 ... 2 GHz	750	58.8 / 61 ±2	20 / 20			
	2 ... 4 GHz	400	56 / 58 ±2	20 / 20			

Standard Specifications:

Input Power:	0 dBm (1 mW) max.
Overdrive Protection:	up to +10 dBm for no damage
Input Impedance:	50 Ohm nominal
Output Impedance:	50 Ohm nominal
Input VSWR:	<2:1 typ.
Load VSWR:	2:1 max. for P _N –0.5 dB infinite for no damage
Spurious (at P _N):	–50 dBc typ. (excluding harmonics)
Class of Operation:	A–linear

General:

RF Input:	N–f (<8 GHz), standard on rear panel SMA–f (8 to 18 GHz), standard on front panel K–f (>18 GHz), standard on front panel
RF Output:	N–f (<8 GHz), standard on rear panel SMA–f (8 to 18 GHz), standard on front panel

BONN Elektronik GmbH – BLMA 1 ... 4 GHz

Mains Supply:	K-f (>18 GHz), standard on front panel Line Power: <1000 W 100 ... 240 V AC $\pm 10\%$ / 47 ... 63 Hz Line Power: 1000 ... 3000 W 200 ... 240 V AC $\pm 10\%$ / 47 ... 63 Hz Line Power: >3000 W 3x 400 V AC $\pm 10\%$ / 47 ... 63 Hz
Elapsed Time Meter:	via status display
Ambient Temperature:	0 ... +45 °C
Storage Temperature:	–20 ... +85 °C
Relative Humidity:	up to 95% (non-condensing)
Operating Altitude:	up to 2000 m above sea level
Vibration and Shock:	MIL-STD-810 F
Cooling:	forced air with integral blower, air intake from front air exhaust at rear

Options:

A) RF Monitor Outputs	G) Output Isolator
B) External Dual Directional Coupler	H) DC-Supply
C) IEEE-488.2 GPIB Remote Control	I) 3x 200 V AC / 60 Hz
D) Front Panel RF-Connectors	R) RS-232C Remote Control
E) Power Indication (digital)	U) USB Remote Control
F) Gain Adjustment	

Specifications are subject to change without notice



Rudolf-Diesel-Str.18 · D-85521 Ottobrunn · Tel +49 (0)89/608 754-0 · Fax +49 (0)89/608 754-99
email: info@bonn-elektronik.com · home: www.bonn-elektronik.com