

BSA

9 kHz ... 1000 MHz

Solid State

Standard Models

Model	Frequency Range	Output Power P_N min W	Gain min / typ dB	Harmonics 2nd / 3rd dBc	Line Power W	Dimensions (H, D) 19"-System	Weight kg
BSA 0101-5	9 kHz ... 1000 MHz	5	37 / 39 ± 2	20 / 20	100	3 HU, 350 mm	11
BSA 0101-7.5	9 kHz ... 1000 MHz	7.5	38.8 / 41 ± 2	20 / 20	100	3 HU, 350 mm	12
BSA 0101-10	9 kHz ... 1000 MHz	10	40 / 42 ± 2	20 / 20	150	3 HU, 350 mm	13
BSA 0101-25/30D	9 kHz ... 1000 MHz	25/30			180	3 HU, 550 mm	18
	9 kHz ... 250 MHz	25	44 / 46 ± 2	20 / 20			
	200 ... 1000 MHz	30	44.8 / 47 ± 2	20 / 20			
BSA 0101-75/60D	9 kHz ... 1000 MHz	75/60			450	4 HU, 550 mm	26
	9 kHz ... 250 MHz	75	48.8 / 51 ± 2	20 / 20			
	200 ... 1000 MHz	60	47.8 / 50 ± 2	20 / 20			
BSA 0101-150/120D	9 kHz ... 1000 MHz	150/120			900	5 HU, 630 mm	46
	9 kHz ... 250 MHz	150	51.8 / 54 ± 2	20 / 18			
	200 ... 1000 MHz	120	50.8 / 53 ± 2	20 / 15			

Standard Specifications:

Input Power:	0 dBm (1 mW) max.
Overdrive Protection:	up to +10 dBm for no damage
Input Impedance:	50 Ohm nominal
Output Impedance:	50 Ohm nominal
Input VSWR:	<2:1 typ.
Load VSWR:	2:1 max. for P_N -0.5 dB; infinite for no damage
Spurious (at P_N):	-50 dBc typ.(excluding harmonics)

Class of Operation: A-linear

General:

RF Input:	N-f; standard on rear panel
RF Output:	N-f; standard on rear panel
Mains Supply:	Line Power: <1000 W 100 ... 240 V AC $\pm 10\%$ / 47 ... 63 Hz Line Power: 1000 ... 3000 W 200 ... 240 V AC $\pm 10\%$ / 47 ... 63 Hz Line Power: >3000 W 3x 400 V AC $\pm 10\%$ / 47 ... 63 Hz
Elapsed Time Meter:	via status display
Ambient Temperature:	0 ... +45 °C
Storage Temperature:	-20 ... +85 °C
Relative Humidity:	up to 95% (non-condensing)
Operating Altitude:	up to 2000 m above sea level
Vibration and Shock:	MIL-STD-810 F
Cooling:	forced air with integral blower, air intake from front air exhaust at rear

Options:

A) RF Monitor Outputs	F) Gain Adjustment
B) External Dual Directional Coupler	H) DC-Supply
C) IEEE-488.2 GPIB Remote Control	R) RS-232C Remote Control
D) Front Panel RF-Connectors	U) USB Remote Control
E) Power Indication (digital)	

Specifications are subject to change without notice

BONN Elektronik GmbH – BSA 9 kHz ... 1000 MHz



Rudolf-Diesel-Str.18 · D-85521 Ottobrunn · Tel +49 (0)89/608 754-0 · Fax +49 (0)89/608 754-99
email: info@bonn-elektronik.com · home: www.bonn-elektronik.com