

Cellular Bands

2,3 ... 2,5 GHz

Standard Models

Model	Frequency Range	Output Power P _N min W	Gain min / typ dB	Harmonics 2nd / 3rd dBc	Line Power W	Dimensions (H,D) 19"-System	Weight kg
BLMA 2325–10	2,3 ... 2,5 GHz	10	40 / 42 ±2	50 / 50	80	3 HU, 350 mm	12
BLMA 2325–25	2,3 ... 2,5 GHz	25	44 / 46 ±2	50 / 50	180	3 HU, 350 mm	18
BLMA 2325–50	2,3 ... 2,5 GHz	50	47 / 49 ±2	50 / 50	400	3 HU, 550 mm	25
BLMA 2325–100	2,3 ... 2,5 GHz	100	50 / 52 ±2	50 / 50	800	3 HU, 550 mm	28
BLMA 2325–150	2,3 ... 2,5 GHz	150	51.8 / 54 ±2	50 / 50	1500	4 HU, 630 mm	45

Standard Specifications:

Input Power:	0 dBm (1 mW) max.
Overdrive Protection:	up to +10 dBm for no damage
Input Impedance:	50 Ohm nominal
Output Impedance:	50 Ohm nominal
Input VSWR:	<2:1 typ.
Load VSWR:	2:1 max. for P _N –0.5 dB infinite for no damage
Spurious (at P _N):	–50 dBc typ.(excluding harmonics)
Class of Operation:	A–linear (GHz) A–B linear (GHz)

General:

RF Input:	N–f; standard on rear panel
RF Output:	N–f; standard on rear panel

BONN Elektronik GmbH – Cellular Bands 2,3 ... 2,5 GHz

Mains Supply:	Line Power: <1000 W 100 ... 240 V AC \pm 10% / 47 ... 63 Hz Line Power: 1000 ... 3000 W 200 ... 240 V AC \pm 10% / 47 ... 63 Hz Line Power: >3000 W 3x 400 V AC \pm 10% / 47 ... 63 Hz
Ambient Temperature:	0 ... +45 °C
Storage Temperature:	-20 ... +85 °C
Relative Humidity:	up to 95% (non-condensing)
Operating Altitude:	up to 2000 m above sea level
Vibration and Shock	MIL-STD-810 F
Cooling:	forced air with integral blower, air intake from front air exhaust at rear

Options:

- | | |
|--------------------------------------|---------------------------|
| A) RF Monitor Outputs | F) Gain Adjustment |
| B) External Dual Directional Coupler | G) Output Isolator |
| C) IEEE-488.2 GPIB Remote Control | H) DC-Supply |
| D) Front Panel RF-Connectors | R) RS-232C Remote Control |
| E) Power Indication (digital) | U) USB Remote Control |

Specifications are subject to change without notice

BONN Elektronik GmbH – Cellular Bands 2,3 ... 2,5 GHz



Rudolf-Diesel-Str.18 · D-85521 Ottobrunn · Tel +49 (0)89/608 754-0 · Fax +49 (0)89/608 754-99
email: info@bonn-elektronik.com · home: www.bonn-elektronik.com