

TWAL

8 ... 18 GHz

Travelling Wave Tube

Standard Models

Model	Frequency Range	Output Power P _N min W	Gain min / typ dB	Harmonics 2nd / 3rd dBc	Line Power W	Dimensions (H,D) 19"-System	Weight kg
TWAL 0818-20	8 ... 18 GHz	20	43 / 51 ±7.5	10 / 20	400	3 HU, 550 mm	20

Standard Specifications:

Input Power	0 dBm (1 mW) max.
Overdrive Protection:	up to +10 dBm for no damage
Input Impedance:	50 Ohm nominal
Output Impedance:	50 Ohm nominal
Input VSWR:	<2:1 typ.
Load VSWR:	2:1 max. for P _N -0.5 dB infinite for no damage
Spurious (at P _N):	-50 dBc typ.(excluding harmonics)
Noise Figure:	20 dB max.
Class of Operation:	A-linear

General:

RF Input:	N-f; standard on rear panel
RF Output:	N-f; standard on rear panel
Mains Supply:	200 ... 264 V AC / 47 ... 63 Hz
Elapsed Time Meter:	via status display
Ambient Temperature:	0 ... +40 °C
Storage Temperature:	-20 ... +85 °C

BONN Elektronik GmbH – TWAL 8 ... 18 GHz

Relative Humidity:	up to 95% (non-condensing)
Operating Altitude:	up to 2000 m above sea level
Vibration and Shock:	normal laboratory environment
Cooling:	forced air with integral blower, air intake and exhaust at rear

Options:

- | | |
|--------------------------------------|----------------------------|
| A) RF Monitor Outputs | G) Output Isolator |
| B) External Dual Directional Coupler | M) 115 V AC / 47 ... 63 Hz |
| C) IEEE-488.2 GPIB Remote Control | N) Harmonic Filter |
| D) Front Panel RF Connectors | R) RS-232C Remote Control |
| E) Power Indication (digital) | U) USB Remote Control |
| F) Gain Adjustment | |

Specifications are subject to change without notice



Rudolf-Diesel-Str.18 · D-85521 Ottobrunn · Tel +49 (0)89/608 754-0 · Fax +49 (0)89/608 754-99
email: info@bonn-elektronik.com · home: www.bonn-elektronik.com